

**BOB'S FOAM FACTORY  
4055 PESTANA PLACE  
FREMONT, CA 94538  
510-657-2420  
510-657-2423 (FAX)**

**FOAMEX GRADE H-290-55-Y6**

**Q-61 HRF- SPECS**

**Tests performed to ASTM D-3574 Standards**

<b>Density, lbs/cu. Ft.</b>	<b>2.80 – 3.00</b>
<b>ILD, lbs/50 sq. in. @ 25% (4")</b>	<b>52.0 – 58.0</b>
<b>SUPPORT FACTOR</b>	<b>2.25</b>
<b>Hysterisis Loss @ 25%</b>	<b>35% Max.</b>
<b>Tear Strength, lbs/linear in.</b>	<b>1.10 PLI Min.</b>
<b>Tensile Strength, lbs/sq. in.</b>	<b>10.0 PSI Min.</b>
<b>Elongation, %</b>	<b>90 - 125</b>
<b>Resilience, %</b>	<b>Greater than 40</b>
<b>Compression Set, 90%, 22hrs, 158°F</b>	<b>less than 10%</b>

**Color – Yellow**

**UA or H – High resilent Foam, Excellent for use in furniture applications.**

**Passes Flammibility requirements for California Technical Bulletin 117 – Sec A,  
Part 1; Sec D, Part II**